

OT 20/200...240/24

Kod produktu: 56411



Dane techniczne:

- Power factor λ **0.80**
- Length **109.0 mm**
- Nominal output power **20 W**
- Input voltage AC **198□254 V**
- Device power loss **4.0 W**
- ECG efficiency **83 %**
- Nominal current **0.35 A**
- Inrush current **10 A**
- Max. no. of ECGs on circuit breaker 10 A **42**
- Galvanic isolation primary/secondary **3 kV**
- Max. no. of ECGs on circuit breaker 16 A **68**
- Surge capability (L-N) **1 kV**
- Width **50.0 mm**
- Height **35.0 mm**
- Cable cross-section, input side **0.75□1.5 mm²**
- Product weight **108.00 g**
- Cable cross-section, output side **0.5□1.5 mm²**
- Casing material **Plastic**
- Wire preparation length, input side **10 mm**
- Ambient temperature range **-20□+45 °C**
- Maximum temperature at tc test point **70 °C**
- ECG lifetime **30000 h**
- Max.housing temperature in case of fault **90 °C**
- Suitable for fixtures with prot. class **II**
- Approval marks □ approval **CE / ENEC 10 / VDE / VDE-EMC / GOST / C-Tick**
- Standards **Acc. to IEC 61347-2-13/Acc. to IEC 62384/Acc. to EN 55015/Acc. to IEC 61000-3-2/Acc. to IEC 61000-3-3/Acc. to IEC 61547**
- Type of protection **IP20**
- Nominal voltage **220□240 V**
- Mains frequency **50□60 Hz**
- Nominal output voltage **24 V**
- Dimmable **Yes**
- Overheating protection **Automatic reversible**
- Max. cable length to lamp/LED module **10 m**
- No-load proof **Yes**

- Overload protection **Automatic reversible**
- Short-circuit protection **Automatic reversible**
- Temperature range at storage **-40 to 85 °C**

Product benefits

- Very high efficiency and reliability
- Versatile scope of application due to output power range of up to 240 W
- Constant luminous flux for very low and high temperatures due to Smart Power Supply

Areas of application

- Suitable for indoor and outdoor SELV installations
- Suitable for use in tight, flat luminaires or installation in suspended ceilings
- Outdoor applications only in suitable luminaires

