

DALI Highbay Adapter

Kod produktu: 56758



Dane techniczne:

- Nominal voltage **20.00 V**
- Mains frequency **0 Hz**
- System wattage **0.10 W**
- Length **139.0 mm**
- Width **118.0 mm**
- Height **37.0 mm**
- Product weight **74.00 g**
- Dimming interface **DALI**
- Type of installation **On-top ceiling mounting**
- Maximum installation height **13 m**
- Operating range, light sensor **2001200 lx**
- Type of protection **IP20**
- Product color **White**
- Ambient temperature range **00+50 °C**

Product benefits

- Sensor integration in DALI
- Embedding of HIGH BAY and VISION motion sensors into DALI
- Extended terminal section enables mains looping
- Daylight-dependent control with automatic shutdown in adequate daylight
- DALI based light management system integrable into building management systems
- Flexible addressing via DALI

Areas of application

- Industry
- Production halls
- Sports halls
- Logistic centers
- Areas with high ceilings
- Connection of light and presence sensors in DALI systems
- Suitable for indoor installations
- Production and assembly facilities

Product features

- DALI adapter for HIGH BAY and VISION sensor
- Direct connection to DALI
- Connection via screwless push wire terminals
- Light sensor working range: 20...800 lx (measured at sensor)
- Integrated light sensor
- Suitable for through wiring
- Suitable for daylight-dependent control
- Light regulation for mounting heights of up to 13 m
- Power supply for coupler from DALI
- Integration into BMS systems

Equipment / Accessories

- Blind cover included
- Can be used with DALI Professional light control system

