

DALleco Control

Kod produktu: 56771



Dane techniczne:

- Nominal voltage **230.00 V**
- Mains frequency **50±60 Hz**
- System wattage **4.00 W**
- Length **118.0 mm**
- Width **30.0 mm**
- Height **21.0 mm**
- Product weight **48.50 g**
- Dimming interface **DALI**
- Type of installation **Luminaire integration**
- Number of control outputs **2**
- Type of protection **IP20**
- Ambient temperature range **-20±50 °C**

Product benefits

- VDE/VDE EMC certified system
- Simplified startup thanks to predefined operation modes
- Automatic and manual setting of regulation set point

Areas of application

- Offices
- Classrooms
- Training rooms
- Corridors
- Ceiling or independent installation via ECO CI KIT possible

Product features

- 2 channel light control with DALI interface
- Daylight-dependent regulation and presence-dependent control of light
- 100 hours burn-in function for fluorescent lamps
- Operation via standard pushbutton or IR remote control
- Outputs with adjustable offset
- Outputs with electronical reversible overtemperature, short-circuit, overload protection

- Connection of up to 4 DALIeco LS/PD LI or 6 DALI LS/PD LI sensors
- Connection of up to 4 light and presence sensors via 4p4c plug system
- Individual adjustment of functional parameters via IR remote control
- Halogen free polycarbonate plastic housing
- Sensor connection via polarity reversal protected 4p4c socket (RJ10)

Equipment / Accessories

- Suitable for up to 32 electronic control gears

