

TCW216 2xTL-D36W HFS PI

Kod produktu: 58732



Dane techniczne:

- Dimmable **No [No]**
- Full product code **910402607118**
- Full product name **TCW216 2xTL-D36W HFS PI**
- Order code **910402607118**
- Order product name **TCW216 2xTL-D36W HFS PI**
- Pieces per pack **0**
- Bar code on outerbox - EAN3 **8711559103471**
- Packs per outerbox **1**
- Logistic code(s) - 12NC **910402607118**
- Net weight per piece **2.203 kg**
- Product family code **TCW216 [TCW216]**
- Number of light sources **2 [2 pcs]**
- Lamp family code **TL-D [MASTER TL-D]**
- Lamp power **36 W [36 W]**
- Compensation circuit **No**
- Gear **HFP [HF Performer]**
- Optic type **No**
- Emergency lighting **No**
- Feed-through wiring **No**
- Ingress protection code **IP66 [Dust penetration-protected, jet-proof]**
- Input voltage **220-240 V [220 to 240 V]**
- Protection class IEC **CLI [Safety class I]**
- Mech. impact protection code **IK08 [5 J vandal-protected]**
- CE mark **CE [CE mark]**
- ENEC mark **ENEC [ENEC mark]**
- Flammability mark **F [For mounting on normally flammable surfaces]**
- Glow-wire test **850/5 [Temperature 850 °C, duration 5 s]**
- Light source replaceable **true [Yes]**
- Connection **PI [Push-in connector 3-pole]**
- Driver included **true [Yes]**
- Housing material **PES [Polyester]**
- Ready-to-install **No**
- Electrical circuit protection **No**
- Explosion hazard class **No**
- Country version **No**

- Housing configuration 2 **H2L [2-lamp housing]**
- Mechanical accessories **No**

TCW216 - 2 pcs - MASTER TL-D - 36 W - HF Performer

Pacific TCW216 is a functional dust-, jet-, shock- and vandalproof luminaire, and can accommodate both TL-D and TL5 (16 mm) fluorescent lamps. The cover is fixed to the housing by means of an innovative concept using integrated fixing points to avoid external lockers. There is a choice of different standard versions available. The luminaire can be mounted individually or in-line with easy 'click' installation. Flexibility is ensured with a choice of fixing points and different cable entries. The TCW216 can also be suspended from Philips TTX410 light-line systems.

Features

Dust-, jet-, shock- and vandal-proof
 TL-D or TL5 (16 mm) fluorescent lamps
 Mounting individually or in lines
 Also available in versions for cold stores (-20 °C)

Applications

Industry
 Indoor workplaces
 Parking garages
 Cold stores -20°C (XAP)





