

Uni LED 44W 3000K MPRM

Kod produktu: 62564



Dane techniczne:

- Light source power **1x44W**
- Louver/shutter **MPRM**
- Luminaire luminous efficacy **93 lm/W**
- Luminaire luminous flux **4100 lm**
- Color temperature **3000K**
- Weight **5.50 kg**
- Type of installation **Universal mounting**
- Housing material **Steel sheet**
- Reflector **None**
- Light source **LED**
- Number of light sources **1**
- Type of equipment **AC**
- Voltage rating **230 V**
- Light source included **Yes**
- Type of LED **LG6030**
- SELV **Yes**
- Light source power **44W**
- Luminaire power **44 W**
- Color **White**
- Light color **White**
- Color rendering index **80**
- Class of luminaire **I**
- Light distribution **DI**
- Degree of protection (IP) **IP20**
- Class of protection **I**
- Energy class **A+**
- CE **Yes**
- Light source protection **Yes**

Universal luminaire designed specifically for LED light sources. Simple installation, LED chips of reputable manufacturers and power factor $\cos \phi = 0,97$ makes the UNI LED a high quality product with a wide range of possible applications. UNI LED was designed especially for offices, conference rooms and pedestrian walkways and is available in versions with motion sensor and emergency module.

Materials: powder painted housing made of galvanized steel sheets (standard color: white), frame on magnets with

protection against falling, opal, prismatic PRM or microprismatic MPRM diffuser

Installation: suspended, for 600x600 ceiling, ceiling mounted

L	W	H
595	595	45
L - Length		
W - Width		
H - Height / Depth		

