

Matrius 35W 4000K IP65 45° Frosted

Kod produktu: 62960



Dane techniczne:

- Light source power **1x35W**
- Info **Frosted**
- Luminarie luminous efficacy **61 lm/W**
- Luminarie luminous flux **2750 lm**
- Color temperature **4000K**
- Weight **3.10 kg**
- Beam angle **45°**
- Degree of protection (IP) **IP65**
- Type of installation **Universal mounting**
- Housing material **Aluminum**
- Diffuser color **None**
- Louver/shutter **Transparent plastic**
- Diffuser material **Transparent plastic**
- Light source **LED**
- Number of light sources **1**
- Type of equipment **AC**
- Voltage rating **230 V**
- Light source included **Yes**
- Power factor **0.97**
- SELV **Yes**
- Color **Grey**
- Light color **White**
- Color rendering index **80**
- Class of luminarie **I**
- Light distribution **DI**
- Class of protection **I**
- Energy class **A+**
- CE **Yes**
- Light source protection **Yes**

Modern, hermetic luminaire with multiple functions. Perfect for lighting aisles, passageways, storage areas, warehouses and all types of industrial spaces. Matrius is equipped with the latest generation of LED sources closed in the aesthetic, aluminum housing with IP54 degree of protection. Easy installation and smooth adjustment of fasteners spacing.

Materials: aluminum profile, transparent polycarbonate diffuser

Installation: suspended, ceiling mounted, wall mounted (additional wall bracket, possibility of installation only with luminaire pointing down)

Power: 230 V

	L	W	H
PX4010152 35W	900	62	93
PX4010159 45W	1200	62	93
PX4010166 55W	1490	62	93
PX4010101 35W	900	62	93
PX4010108 45W	1200	62	93
PX4010115 55W	1490	62	93
PX4010201 35W	900	62	93
PX4010207 45W	1200	62	93
PX4010213 55W	1490	62	93
PX4010219 35W	900	62	93
PX4010225 45W	1200	62	93
PX4010231 55W	1490	62	93
PX4010321 35W	900	62	93
PX4010328 45W	1200	62	93
PX4010335 55W	1490	62	93
PX4010342 35W	900	62	93
PX4010349 45W	1200	62	93
PX4010356 55W	1490	62	93
PX4010363 35W	900	62	93
PX4010370 45W	1200	62	93
PX4010377 55W	1490	62	93
PX4010384 35W	900	62	93
PX4010391 45W	1200	62	93
PX4010398 55W	1490	62	93

L - Length

W - Width

H - Height / Depth



