

# LED luminaire With Bridgelux LEDs 112W neutral white

Kod produktu: 69072



## Dane techniczne:

- Dostępność w magazynie
- Light source **112xLED**
- Power **112W**
- Luminous flux **11200lm**
- Color temperature **4000-4500K**
- Supply Voltage **230V AC**
- Class of protection **I**
- Compliance with European standards (CE) **YES**
- IP degree of protection **IP65**
- Way of mounting **the mast (boom levels)**
- Light source **Power LED Bridgelux**
- Color **silver**
- Beam angle **120°/60°**

Dimensions: 610×315×80

- Adapter included: Mean Well
- Power factor: > 0.95
- Housing material: aluminum alloy
- Color: silver
- Diffuser (bowl): transparent glass
- Mounted on a mast: boom levels
- Mounting Bracket: solid
- Adjustable slope angle: no
- Fire protection class: I
- Temperature: -40 ° to + 50 ° C
- Certificates: CE, RoHS



**Lampa uliczna - z diodami BRIDGELUX**



Wapienie: opłaskić  
 Złoto: nie myć  
 Włókno szklane: nie myć  
 Kolor obudowy: srebrny  
 Średnica obudowy: Ø160  
 Wykończenie: lakier  
 Wykonanie: stal nierdzewna  
 Waga netto z przewodami: 1,1 kg  
 Wykonanie: stal nierdzewna  
 Ciężar brutto: 1,3 kg

2000h, 20%  
 -0,30  
 2000 godzin  
 2000h  
 2000h

Model	Wzrost	Waga	Temperatura pracy	IP	Wzrost	Wzrost	Wzrost	Wzrost	Wzrost	Wzrost
000101	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000102	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000103	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000104	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000105	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000106	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000107	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000108	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000109	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000110	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000111	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000112	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000113	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000114	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000115	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000116	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000117	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000118	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000119	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000120	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000121	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000122	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000123	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000124	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000125	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000126	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000127	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000128	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000129	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	
000130	16	1000	4000-4500K	-15	120°/30°	16	Przewod 2x100-300mm	400-1200mm	2000h-50k	