

# LUGCLASSIC LED 625x625 recessed ED 9600lm/830 PLX IP44 white

Kod produktu: 70214



## Dane techniczne:

- Lumen LED[lm] **9600**
- Luminaire power [W] **74**
- Power LED[W] **62**
- CRI/Ra > **80**
- Colour temperature [K] **3000**
- Efficacy[lm/W] **114**
- Lumen luminaire[lm] **8400**
- Mounting **directly in the ceiling construction**
- Body **powder-painted steel sheet**
- Includes light source **yes**
- Application **offices, hospitals, laboratories, supermarkets, classrooms, auditorium**
- Available on request **emergency kit LED, luminaires for KNAUF, AMF, ROCKFON ceilings (on request)**

Due to excellent efficacy and quality, the luminaire meets the requirements of the most demanding lighting projects, high quality diffuser providing balanced uniformity and high luminaire efficiency of more than 100lm/W.

Code	Dimensions [mm] L W H D	Pallet quantity	Quantity in package	Net weight[kg]
060141.5L05. 315	595 595 72 10 32 3		1	4,5
060141.5L06. 315	595 595 72 10 32 3		1	4,5
060141.5L07. 315	595 595 72 10 32 3		1	4,5
060141.5L08. 315	595 595 72 10 32 3		1	4,5
060141.5L05. 325	622 622 63 93 32 325		1	4,7
060141.5L06. 325	622 622 63 93 32 325		1	4,7
060141.5L07. 325	622 622 63 93 32 325		1	4,7
060141.5L08. 325	622 622 63 93 32 325		1	4,7

Code	Dimensions [mm] L W H D	Pallet quantity	Quantity in package	Net weight[kg]
325				

