

ATLANTYK STRONG LED 1299 ED 7400lm/840 PMMA opal IP65

Kod produktu: 70411



Dane techniczne:

- Lumen LED[lm] **7400**
- Luminaire power [W] **53**
- Power LED[W] **45**
- CRI/Ra > **80**
- Colour temperature [K] **4000**
- Efficacy[lm/W] **125**
- Lumen luminaire[lm] **6640**
- Body **polyester material reinforced with fibreglass**
- Mounting **directly on the ceiling, suspended, with mounting brackets (included)**
- Power supply efficiency >**89%**
- Electrical connection **tight connector 5x2,5 mm²**
- Includes light source **yes**
- Warranty **3 years + 2 years after project registration**
- Application **industrial facilities, warehouses, parking areas, laboratories, metro**
- Available on request **LED emergency module**
- Additional equipment **stainless steel clips**
- Lifetime **50 000 h**
- Other remarks **In case of application of the luminaires in hard chemical environment please contact LUG Technical Department or check Chemical Resistance table - available both, in the catalogue and on our website.**

ATLANTYK STRONG LED is an industrial luminaire for LED light sources, water-jet protected with an increased chemical resistance, dedicated to use in extreme environments. Best in class, with outstanding parameters of lighting, ensures high performance and short payback period.

| Code | Dimensions [mm] L W H D | Pallet quantity | Quantity in package | Net weight[kg] |
|-----------------------------|----------------------------|-----------------|---------------------|----------------|
| Type of equipment: STANDARD | | | | |
| 090250.5L01.711 | 1299 85 92 700 | 152 | 1 | 2,0 |
| 090250.5L03.711 | 1299 85 92 700 | 152 | 1 | 2,0 |
| 090250.5L04.711 | 1299 85 92 700 | 152 | 1 | 2,0 |
| 090250.5L05.711 | 1299 85 92 700 | 152 | 1 | 2,0 |
| 090250.5L06.711 | 1299 85 92 700 | 152 | 1 | 2,0 |

| | | | | |
|--|----------------|-----|---|-----|
| 090250.5L08.711 | 1299 85 92 700 | 152 | 1 | 2,0 |
| 090250.5L09.711 | 1299 85 92 700 | 152 | 1 | 2,0 |
| 090250.5L10.711 | 1299 85 92 700 | 152 | 1 | 2,0 |
| Type of equipment: Radar motion detector | | | | |
| 090250.5L01.711.920 | 1299 85 92 700 | 152 | 1 | 2,0 |
| 090250.5L03.711.920 | 1299 85 92 700 | 152 | 1 | 2,0 |
| 090250.5L04.711.920 | 1299 85 92 700 | 152 | 1 | 2,0 |
| 090250.5L05.711.920 | 1299 85 92 700 | 152 | 1 | 2,0 |
| 090250.5L06.711.920 | 1299 85 92 700 | 152 | 1 | 2,0 |
| 090250.5L08.711.920 | 1299 85 92 700 | 152 | 1 | 2,0 |
| 090250.5L09.711.920 | 1299 85 92 700 | 152 | 1 | 2,0 |
| 090250.5L10.711.920 | 1299 85 92 700 | 152 | 1 | 2,0 |
| Type of equipment: through wiring | | | | |
| 090250.5L01.711.938 | 1299 85 92 700 | 152 | 1 | 2,1 |
| 090250.5L03.711.938 | 1299 85 92 700 | 152 | 1 | 2,1 |
| 090250.5L04.711.938 | 1299 85 92 700 | 152 | 1 | 2,1 |
| 090250.5L05.711.938 | 1299 85 92 700 | 152 | 1 | 2,1 |
| 090250.5L06.711.938 | 1299 85 92 700 | 152 | 1 | 2,1 |
| 090250.5L08.711.938 | 1299 85 92 700 | 152 | 1 | 2,1 |
| 090250.5L09.711.938 | 1299 85 92 700 | 152 | 1 | 2,1 |
| 090250.5L10.711.938 | 1299 85 92 700 | 152 | 1 | 2,1 |
| Type of equipment: EM 1h | | | | |
| 090250.5L01A.711 | 1299 85 92 700 | 152 | 1 | 2,5 |
| 090250.5L03A.711 | 1299 85 92 700 | 152 | 1 | 2,5 |
| 090250.5L04A.711 | 1299 85 92 700 | 152 | 1 | 2,5 |
| 090250.5L05A.711 | 1299 85 92 700 | 152 | 1 | 2,5 |
| 090250.5L06A.711 | 1299 85 92 700 | 152 | 1 | 2,5 |
| 090250.5L08A.711 | 1299 85 92 700 | 152 | 1 | 2,5 |
| 090250.5L09A.711 | 1299 85 92 700 | 152 | 1 | 2,5 |
| 090250.5L10A.711 | 1299 85 92 700 | 152 | 1 | 2,5 |
| Type of equipment: EM 3h | | | | |
| 090250.5L01B.711 | 1299 85 92 700 | 144 | 1 | 3,0 |
| 090250.5L03B.711 | 1299 85 92 700 | 144 | 1 | 3,0 |
| 090250.5L04B.711 | 1299 85 92 700 | 144 | 1 | 3,0 |
| 090250.5L05B.711 | 1299 85 92 700 | 144 | 1 | 3,0 |
| 090250.5L06B.711 | 1299 85 92 700 | 144 | 1 | 3,0 |
| 090250.5L08B.711 | 1299 85 92 700 | 144 | 1 | 3,0 |
| 090250.5L09B.711 | 1299 85 92 700 | 144 | 1 | 3,0 |
| 090250.5L10B.711 | 1299 85 92 700 | 144 | 1 | 3,0 |



