

CARO 1 LED bracket ED 230V/50Hz 6x2W red IP65 45st. grey

Kod produktu: 70896



Dane techniczne:

- Lumen LED[lm] **270**
- Luminaire power [W] **8**
- Power LED[W] **6**
- Efficacy[lm/W] **25**
- Lumen luminaire[lm] **200**
- Mounting **surface mounted**
- Body **high pressure die-cast aluminum**
- Includes light source **yes**
- Power supply efficiency **>71%**
- Electrical connection **3x2,5 mm² wire**
- Warranty **3 years + 2 years after project registration**
- Application **facades, hotels, shopping centers, restaurants, museums**
- Lifetime **50 000 h**

Wall luminaires being perfect solution for facade illumination - different beam angles and LED colors possible.

| Code | Dimensions [mm] L W H D | Dimensions de découpe [mm] H D | Pallet quantity | Quantity in package | Net weight[kg] |
|------------------|----------------------------|-----------------------------------|-----------------|---------------------|----------------|
| 140122.5L011.604 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L011.607 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L011.608 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L012.604 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L012.607 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L012.608 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L013.604 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L013.607 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L013.608 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L014.604 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L014.607 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L014.608 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L015.604 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L015.607 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |
| 140122.5L015.608 | 270 150 200 100 | 80 60 | 112 | 1 | 3,2 |

| Code | Dimensions [mm] W H D | L | Dimensions de découpe [mm] H D | Pallet quantity | Quantity in package | Net weight[kg] |
|------------------|--------------------------|----|-----------------------------------|-----------------|---------------------|----------------|
| 140122.5L016.604 | 270 150 200 100 | 80 | 60 | 112 | 1 | 3,2 |
| 140122.5L016.607 | 270 150 200 100 | 80 | 60 | 112 | 1 | 3,2 |
| 140122.5L016.608 | 270 150 200 100 | 80 | 60 | 112 | 1 | 3,2 |

